

ROXXY-POWER ZX Serie 25/50 C

No.	Cells	Capacity(mAh)	Charge current				Discharge current				Dimensions			Weight (g)
			Normal		Maximal		Normal		Maximal		L	W	H	
			C	A	C	A	C	A	C	A	mm			
4859	2	350	1	0,35	4	1,4	25C	8,8	50C	17,5	52	30	8,5	27
4860	3	350	1	0,35	4	1,4	25C	8,8	50C	17,5	52	30	17	39
4861	2	500	1	0,50	4	2,0	25C	12,5	50C	25,0	52	30	10	31
4862	3	500	1	0,50	4	2,0	25C	12,5	50C	25,0	52	30	15	46
4863	2	800	1	0,80	4	3,2	25C	20,0	50C	40,0	52	30	14	45
4864	3	800	1	0,80	4	3,2	25C	20,0	50C	40,0	52	30	21	66
4865	2	1000	1	1,00	4	4,0	25C	25,0	50C	50,0	74	35	12	≤55
4866	3	1000	1	1,00	4	4,0	25C	25,0	50C	50,0	74	35	18	≤83
4867	2	1300	1	1,30	4	5,2	25C	32,5	50C	65,0	70	35	14	75
4868	3	1300	1	1,30	4	5,2	25C	32,5	50C	65,0	72	35	21	111
4869	2	1500	1	1,50	4	6,0	25C	37,5	50C	75,0	100	35	11	83
4870	3	1500	1	1,50	4	6,0	25C	37,5	50C	75,0	100	35	17	124
4871	2	2200	1	2,20	4	8,8	25C	55,0	50C	110,0	103	35	15	117
4872	3	2200	1	2,20	4	8,8	25C	55,0	50C	110,0	103	35	23	171
4873	4	2200	1	2,20	4	8,8	25C	55,0	50C	110,0	104	36	30	221
4874	2	2700	1	2,70	4	10,8	25C	67,5	50C	135,0	132	45	11	153
4875	3	2700	1	2,70	4	10,8	25C	67,5	50C	135,0	132	45	17	231
4876	6	2700	1	2,70	4	10,8	25C	67,5	50C	135,0	132	45	34	428
4877	2	3300	1	3,30	4	13,2	25C	82,5	50C	165,0	134	45	14	183
4878	3	3300	1	3,30	4	13,2	25C	82,5	50C	165,0	136	45	21	257
4879	4	3300	1	3,30	4	13,2	25C	82,5	50C	165,0	136	45	28	351
4880	5	3300	1	3,30	4	13,2	25C	82,5	50C	165,0	136	45	35	445
4881	6	3300	1	3,30	4	13,2	25C	82,5	50C	165,0	136	45	41	526
4882	2	3700	1	3,70	4	14,8	25C	92,5	50C	185,0	140	51	13	216
4883	3	3700	1	3,70	4	14,8	25C	92,5	50C	185,0	143	51	19	301
4884	4	3700	1	3,70	4	14,8	25C	92,5	50C	185,0	143	51	25	392
4885	5	3700	1	3,70	4	14,8	25C	92,5	50C	185,0	146	51	32	491
4886	6	3700	1	3,70	4	14,8	25C	92,5	50C	185,0	144	51	37	583
4887	2	4400	1	4,40	4	17,6	25C	110,0	50C	220,0	141	50	15	238
4888	3	4400	1	4,40	4	17,6	25C	110,0	50C	220,0	142	50	23	354
4889	4	4400	1	4,40	4	17,6	25C	110,0	50C	220,0	142	51	30	464
4890	5	4400	1	4,40	4	17,6	25C	110,0	50C	220,0	143	51	37	586
4891	6	4400	1	4,40	4	17,6	25C	110,0	50C	220,0	143	51	45	688
4892	2	5000	1	5,00	4	20,0	25C	125,0	50C	250,0	141	51	17	263
4893	3	5000	1	5,00	4	20,0	25C	125,0	50C	250,0	141	51	26	393
4894	4	5000	1	5,00	4	20,0	25C	125,0	50C	250,0	142	51	36	518
4895	5	5000	1	5,00	4	20,0	25C	125,0	50C	250,0	143	51	44	648
4896	6	5000	1	5,00	4	20,0	25C	125,0	50C	250,0	143	51	53	781
4897	5	8000	1	8,00	4	32,0	25C	200,0	50C	400,0	148	69	42	977
4898	6	8000	1	8,00	4	32,0	25C	200,0	50C	400,0	148	69	51	1111
4899	6	10000	1	10,00	4	40,0	25C	250,0	50C	500,0	148	69	60	1421

Remark: 350...800 mAh cells with BEC-connector and silicon wires

Other weight values including 20 cm silicon wire

ROXXY-POWER ZY Serie 30/60 C

No.	Cells	Capacity (mAh)	Charge current				Discharge current				Dimensions			Weight (g)
			Normal		Maximal		Normal		Maximal		L	W	H	
			C	A	C	A	C	A	C	A	mm			
6800	2	2200	1	2,2	4	8,8	30C	66	60C	132	100	35	17	117
6801	3	2200	1	2,2	4	8,8	30C	66	60C	132	101	35	26	201
6802	4	2200	1	2,2	4	8,8	30C	66	60C	132	102	36	34	260
6803	2	2700	1	2,7	4	10,8	30C	81	60C	162	134	45	12	161
6804	3	2700	1	2,7	4	10,8	30C	81	60C	162	135	45	18	235
6805	4	2700	1	2,7	4	10,8	30C	81	60C	162	135	45	24	311
6806	5	2700	1	2,7	4	10,8	30C	81	60C	162	135	45	30	385
6807	6	2700	1	2,7	4	10,8	30C	81	60C	162	136	45	36	461
6808	2	3300	1	3,3	4	13,2	30C	99	60C	198	134	45	15	202
6809	3	3300	1	3,3	4	13,2	30C	99	60C	198	137	45	22	307
6810	4	3300	1	3,3	4	13,2	30C	99	60C	198	136	45	29	393
6811	5	3300	1	3,3	4	13,2	30C	99	60C	198	137	45	37	488
6812	6	3300	1	3,3	4	13,2	30C	99	60C	198	137	45	44	562
6813	2	3700	1	3,7	4	14,8	30C	111	60C	222	141	51	14	205
6814	3	3700	1	3,7	4	14,8	30C	111	60C	222	144	51	21	314
6815	4	3700	1	3,7	4	14,8	30C	111	60C	222	144	51	21	427
6816	5	3700	1	3,7	4	14,8	30C	111	60C	222	145	51	34	534
6817	6	3700	1	3,7	4	14,8	30C	111	60C	222	143	51	41	630
6818	2	4500	1	4,5	4	18,0	30C	135	60C	270	141	50	18	286
6819	3	4500	1	4,5	4	18,0	30C	135	60C	270	144	51	25	401
6820	4	4500	1	4,5	4	18,0	30C	135	60C	270	144	51	33	520
6821	5	4500	1	4,5	4	18,0	30C	135	60C	270	144	51	41	648
6822	6	4500	1	4,5	4	18,0	30C	135	60C	270	144	51	49	773
6823	2	5000	1	5,0	4	20,0	30C	150	60C	300	142	51	17	276
6824	3	5000	1	5,0	4	20,0	30C	150	60C	300	145	51	22	432
6825	4	5000	1	5,0	4	20,0	30C	150	60C	300	143	52	37	561
6826	5	5000	1	5,0	4	20,0	30C	150	60C	300	144	52	45	694
6827	6	5000	1	5,0	4	20,0	30C	150	60C	300	145	52	53	810
Inlinepacks														
6828	10	3700	1	3,7	4	14,8	30C	111	60C	222	290	51	34	1070
6829	12	3700	1	3,7	4	14,8	30C	111	60C	222	290	51	82	1260
6830	10	4000	1	4,0	4	16,0	30C	120	60C	240	290	51	39	1200
6831	12	4000	1	4,0	4	16,0	30C	120	60C	240	290	51	45	1384
6832	10	4500	1	4,5	4	18,0	30C	135	60C	270	290	51	41	1300
6833	12	4500	1	4,5	4	18,0	30C	135	60C	270	290	51	49	1546
6834	10	5000	1	5,0	4	20,0	30C	150	60C	300	290	52	45	1388
6835	12	5000	1	5,0	4	20,0	30C	150	60C	300	260	52	53	1620

Weight including 20 cm siliconwires